



CEN R LPNI

The L3Harris RF-7800I-CU Central Unit is the foundation of the net orking intercom s stem. Advanced technolog eliminates background noise, delivering clear voice communications and data-sharing capabilities for up to eight Cre Stations and ten Combat Net Radios. The vehicle's s stem status, Cre Station controls and

indicators are also monitored b the unit for greater control of the s stem. A, light version is available to support voice-onl communication bet een Cre Stations and radio transceivers.

Simple, eas -to-install four- ire high a cable connects the Central Unit and Cre Stations, reducing unnecessar cabin clutter

Po er-ef cient, modular s stem for mission fle ibilit

Soft are-con gurable and upgradeable through a simple, PC-based user interface More ef cient, simultaneous data and voice through a single connection for up to ten radios

Provides po er, programming, and con guration capabilities to Cre Stations and Active Noise Reduction headsets
Integrates Battle Management S stem and Situational A areness applications
Provides duple streams of 64 kbps digiti/ed PCM voice channels, and duple streams of digitals nchronous communication ith data and control signals of the serial as nchronous ports

I , a Ra	· = - + 3	
I A R A (Ma)	- 5, - 5 ₁	
(🚜)	5	
♦	>= \(\chi_{1}=_i\) I	

ی E LC IN R a

The L3Harris RF-7800I-SKA Soft Ke pad Application utili/es Windo s or Android platforms to gain remote control access of the intercom s stem through a smartphone, tablet or laptop. Android compatibilit includes Samsung edge devices.

Full s stem access from an remote location ith LAN connectivit

Secure login through an IP connection allo ing T pe 1 ireless data aveforms

Feature updates including radio remote control and crossbanding



The L3Harris RF-7800I-RD Rotar Dial Unit allo s users to quickl and easil communicate ith their team, make a phone call or respond to an alarm.

Remote radio control of L3Harris radios from Cre Station at distances of up to 2 km*

16 pre-programmable operation modes

Audible messaging technolog eliminates the need for operators to look at a dial to kno hat channel the are on

Status indicators at each dial position to identif radios in use

Æ ►NI

72

Ea a a a The L3Harris RF-7800I-BU Basic Unit provides preprogrammed operation modes through a hands-free plug-and-pla interface.

Remote radio control of L3Harris radios from Cre Station at distances of up to 2 km*
Delivers continuous voice and data communications
Communicate urgent messages quickl and reliabl
Ideal for e ecuting time-sensitive, critical operations





() _ , |



LAUR TO NET TO NET

The L3Harris RF-7800I Tactical Net orking Intercom S stem voice-onl con guration provides clear voice connectivit to ever cre member ithidæt (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37Bcvid.1 (r)-13o(e)-1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37B0 -1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37B0 -1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37B0 -1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.37B0 -1.qdC186 231 0(o)-12p0 -g-1.37B0 -1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.2 (a-10.8n (e of connectivit)) (m)-7. [fn pl Nvei 3H8TD -1.2 (a-10.8n (e of con





