

### KEY BENEFITS

- > Provides freedom of movement with no protruding parts or cumbersome wires or cables
- > Rugged construction and noise cancellation technologies support clear audio in harsh environmental conditions
- > Real-time Push-To-Talk with

GENERAL SPECIFICATIONS	
<b>Dimensions (H x W x D):</b>	3.5 x 3.0 x 0.8 in (88 x 77 x 21 mm)
<b>Approximate Weight:</b>	4.4 oz (125g)
<b>Operating Temperature Range:</b>	-22 to +140°F (-30 to +60°C)
<b>Storage Temperature Range:</b>	-40 to +104°F (-40 to +85°C)
<b>Charging Temperature Range:</b>	+32 to +104°F (0 to +40°C)
<b>AC Charge Range:</b>	100-240V, 50-60 Hz
<b>Drop Performance:</b>	2 meters
<b>PTT Operations:</b>	200 thousand nominal

MICROPHONE SPECIFICATIONS	
<b>Type:</b>	Electret, Omni-directional
<b>Maximum Acoustic Input before Significant Distortion:</b>	120 dB SPL
<b>Frequency Range:</b>	300 to 3600 Hz

SPEAKER SPECIFICATIONS	
<b>Type:</b>	40 mm Moving Coil, 1 Wrms, 2 Wpk, 8 Ohm
<b>Maximum Acoustic Output at 50 cm:</b>	89 dBA (A2DP mode, multitone)
<b>Frequency Range:</b>	300 to 3600 Hz