ROVER® 6Si TRANSCEIVER

The next generation of rugged, all-in-one, transportable ROVER radios

The L3Harris ROVER 6Si is an upgrade to the popular, widely elded ROVER 6i transceiver. Expanded frequencies, additional processing resources for capability growth and other enhanced features set it apart from earlier ROVER products. This rugged and reliable transceiver transforms sensor-to-shooter networking, allowing increased levels of collaboration and interoperability with numerous manned and unmanned airborne platforms.

PRODUCT DESCRIPTION

Designed for air, surface and maritime use, the L3Harris ROVER 6Si Transceiver provides real-time, full-motion video (FMV) and other network data for situational awareness, targeting, battle damage assessment, surveillance, relay, convoy overwatch operations and other situations where eyes-on-target are required. The ROVER 6Si Transceiver has two receiver channels. This frequency and spatial diversity provides link redundancy, robust reception and resiliency to platform shadowing, multi-path interference, line-of-sight blockages and RF interference. With an unmatched waveform set, ROVER 6Si is interoperable with virtually all large airframes, UAVs and targeting pods in theater today.

NOTABLE ENHANCEMENTS

> High-de nition video
> Expanded S-Band and UHF bands
> Signal and waveform search
> Updated digital processing and additional waveforms
> Improved RF performance

POTENTIAL APPLICATIONS

> Man-packable communications
> Tactical Operations Center communications
> Vehicle-mounted communications
> Airborne communications
> Maritime communications

Combining high-def video and radio communications with proven reliability

KEY FEATURES

> Secure digital communications
  - 256-bit AES
> Multiband reception and transmission
  - Five-band operation (UHF, L, S, C and Ku)
> High-de nition video encoding/decoding
> Signal and waveform search
> Transmit capable
  - External transmitter control
  - Transmitter amp blank and enable signals
> Two reception channels
  - Same or different bands
  - Diversity reception from a single data source with two receive antennas
  - Two external receiver interfaces
> Various powering options
  - Accepts 10 to 32 VDC
  - AC/DC battery eliminator
  - BA-5590 battery-compatible
> Web browser GUI control